



| | | | |
|----------------------------------|------------------------|-----------------------|-----------------------|
| Model | AR-75-S | AD-75-S | ADX-75-S |
| HP | 75 | 75 | 75 |
| kW | 56 | 56 | 56 |
| UL Listing Available (upgrade) | Yes | No | No |
| Start Circuit Protection | Good | Excellent | Ultimate |
| Efficiency | >98% | >98% | >98% |
| Idle Power Consumption (kW) * | 2.1 (\$.21/hr) | 2.1 (\$.21/hr) | 2.1 (\$.21/hr) |
| Operating Reliability (hours) | MTBF 50,000 | MTBF 50,000 | MTBF 50,000 |
| Input Voltage | 208-250, 480V optional | 208-250 | 208-250 |
| Approximate Idle Amps | 9.17 | 9.17 | 9.17 |
| Frequency (Hz) | 60 | 60 | 60 |
| Output Voltage | Input Voltage +/- 5% | Input Voltage +/- 5% | Input Voltage +/- 5% |
| Voltage Balance | 0-5% | 0-5% | 0-5% |
| Maximum Starting Current (Amps) | 182 | 182 | 182 |
| Idler RPM | 1750 | 1750 | 1750 |
| Idler Length x Width x Height | 22" x 21.5" x 16.5" | 22" x 21.5" x 16.5" | 22" x 21.5" x 16.5" |
| Panel Height x Width x Depth | 22.5" x 18.5" x 8.25" | 22.5" x 18.5" x 8.25" | 22.5" x 18.5" x 8.25" |
| Idler Color | Baldor Gray | Baldor Gray | Baldor Gray |
| Panel Color | Black | Black | Black |
| Panel Style | NEMA 1 Indoor | NEMA 1 Indoor | NEMA 1 Indoor |
| Idler Style | Fully Guarded | Fully Guarded | Fully Guarded |
| Total Weight (pounds) | 617 | 617 | 617 |